



Marine LCD Monitor

Model: HM-2617



Keypad Functions



- [1] **[[AUTO]] key**: Automatically adjust to the center display; or return to the previous menu.
- [2] **[[MENU]] key**: See the details behind.
- [3] **[[+]] key**: Press [+] key to increase the brightness of the display or flip down the menu.
- [4] **[[−]] key**: Press [-] key to reduce the brightness of the display or flip up the Menu.
- [5] **[[EXIT]] key**: To turn ON/OFF the monitor, but the core board still working.
- [6] **[[⏻]] key**: Exit from current menu, or back to the previous menu.

Features


- ▶ 17 inch High brightness LED backlight ,1080X1024(SXGA) resolution.
- ▶ Wide temperature range and wide angle of view.
- ▶ Support VGA and DVI interface.
- ▶ Power Supply: DC12V~36 V.
- ▶ Adjust brightness by knob.
- ▶ Designed for Counter mounting and Flush mounting.



HM-2617 SPECIFICATIONS

Display Unit	HM-2617
Display Type	Color TFT LCD
Screen Size	17 inch(338mm×270mm)
Display Resolution	1280 × 1024 (SXGA) pixels
Colors	16. 7M
Screen Brightness	550cd/m ²
Viewing Angle	Horizontal:170 degree Vertical: 160 degree
Contrast Ratio	800:1
Video Input	VGA; DVI
Operating Temperature	-15°C ~ +55°C
Storage Temperature	-20°C ~ +60°C
Power Supply	DC12V ~ 36 V
Compatible Resolution	1280*1024; 1024*768; 800*600; 640*480.....
Menu Language	Chinese, English, French,German, Spanish, Italian, Japanese, Korean, Portuguese, Brazil Portuguese


» Perspective Adjustment



Packing List


Main Unit×1set	Power Cable ×1 pc
VGA Cable ×1 pc	User's Manual ×1 pc
Mounting Bracket×2pcs	Wood Screw ×4 pcs
Mounting Bracket Screw (L) with 2pcs of rubber ring x 2 sets	
Mounting Bracket Screw (S) with 2pcs of rubber ring x 2 sets	

» Interface Definition




» Display Unit

Counter Mounting (5.8kg / 12.79lb)



Flush Mounting (4.9kg / 10.8lb)



[Unit: mm]



Dealer: